



Not: Anemostat damperli seçilecekse, kutu yüksekliği ~8cm daha artırılmalıdır.

GOODMAN  
KANAL TİPİ  
SPLIT KLİMA  
A 60-00-02R  
60.000 btu/h




Damper  
Damper  
Damper  
Damper

400 m<sup>3</sup>/h  
A: 30x30




Ø203

400 m<sup>3</sup>/h  
A: 30x30




Ø203

400 m<sup>3</sup>/h  
A: 30x30



Ø203

400 m<sup>3</sup>/h  
A: 30x30




Ø203

800 m<sup>3</sup>/h  
4,5 m/s  
Ø254

800 m<sup>3</sup>/h  
4,5 m/s  
Ø254



800 m<sup>3</sup>/h  
4,5 m/s  
Ø254

800 m<sup>3</sup>/h  
4,5 m/s  
Ø254





Ø203

Ø203



Ø203

Ø203



400 m<sup>3</sup>/h  
A: 30x30



400 m<sup>3</sup>/h  
A: 30x30



400 m<sup>3</sup>/h  
A: 30x30



400 m<sup>3</sup>/h  
A: 30x30

Malzeme listesi

- |             |                  |
|-------------|------------------|
| 4xØ254      | Goodman flex     |
| 8xØ203      | Goodman flex     |
| 8x(30x30)   | Anemostat kutusu |
| 4xØ200-Ø250 | Spirosafe Te     |